



| | | |
|----------------|--|--------------|
| LOCATION | | DATE |
| PREPARED BY | | QUANTITY |
| COMMENTS | | FIXTURE TYPE |
| CATALOG NUMBER | | |

Aeon LED Series AELF

Features

Geometric sloped sided pendant mount fixture is designed for indirect/ direct light output for a wide even light distribution and low profile floating effect. It is available in two widths, 16" and 22" and two finishes, satin aluminum or oil-rubbed bronze. It can be used in various applications including corridors, kitchens and public spaces. This product offers a lift and shift gravity retention diffuser. Fixture mounts to standard junction box (not included).

Construction

Channel is die-formed of 22-gauge steel. Standard mounting holes are provided in the canopy back mounting plate. Decorative frame assembly is .06" extruded aluminum. Power supply connections must be made inside a junction box (not included).

Finish

Channel is finished in lighting grade white baked gloss enamel paint. Frame assembly consists of extruded satin aluminum or applied oil-rubbed bronze with clear lacquer topcoat.

Diffuser

Acrylic diffuser is .125" thick gloss white for the satin aluminum frame and linen pattern white acrylic for the oil-rubbed bronze frame.

Electrical

This unit is direct wired with a constant current low voltage electronic LED driver powered at 120 VAC/60 Hz. (D1)
The driver is dimmable down to 10% of full scale with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer or choose a 120-277V (D2) driver dimmable 0-10V DC.

Lamping

Fixture includes LED modules capable of producing:
16" - 28W, 3000 source lumens
22" - 46W, 5000 source lumens
2700K or 3000K (CCT). Rated for 50,000 Hrs, 90 CRI.

Certification

All fixtures are cETLus listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

4-3/8" H x 16" W x 53-3/8" L
4-3/8" H x 22" W x 53-3/8" L

Ordering Information:

| Series | Size (Inches) | | LED | CCT | Driver | Finish |
|--------|---------------|--------|-----|----------|---------------------------------|----------------------|
| | W | Lumens | | | | |
| AELF | 16 | = 3000 | L | 27 2700K | D1 Voltage (120V TRIAC Dimming) | RB Oil-Rubbed Bronze |
| | 22 | = 5000 | | 30 3000K | | |

Example: AELF163000L30D1SA

