


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 67.13 lm/W
MODEL	EGRF2440LAJUDWH_3000K	I _{max} (cd)	950.5	S/MH(C0/180)	1.26	
NOMINAL POWER(W)	40	LOR(%)	100.0	S/MH(C90/270)	1.25	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	2612.1	η UP,DN(C0-180)	0.0,50.2	
NOMINAL FLUX(lm)	2612.14	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.8	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	120	η down (%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	934.4	933.9	933.7	932.7	932.9	932.7	933.3	933.3	0- 10	89.89	89.89	3.44,3.44
20	885.3	885.6	888.5	883.0	882.9	882.9	883.0	883.2	10- 20	257.5	347.4	13.3,13.3
30	805.7	809.5	810.3	806.0	802.7	802.7	802.9	801.6	20- 30	390.9	738.3	28.3,28.3
40	698.7	704.5	704.4	700.5	696.6	697.1	697.5	694.8	30- 40	472.0	1210	46.3,46.3
50	567.9	573.9	575.2	572.6	568.3	570.0	569.1	564.6	40- 50	490.7	1701	65.1,65.1
60	417.3	423.3	420.3	423.7	421.0	421.9	414.0	414.9	50- 60	443.0	2144	82.1,82.1
70	253.9	258.1	265.4	262.5	261.6	260.1	258.9	250.4	60- 70	335.4	2479	94.9,94.9
80	97.64	0	0	0	107.9	0	0	0	70- 80	123.3	2603	99.6,99.6
90	0.0774	0	0	0	0.0608	0	0	0	80- 90	9.454	2612	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2025-01-20

V(B) Range:-70 - 70DEG
 V(B) Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
 Humidity:65.0%
 Test Distance:8.800m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1203	0
80	2301	0
75	2731	0
70	3038	3175
65	3257	3319
60	3415	3439
55	3530	3550
50	3615	3661
45	3681	3702


H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0														
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
ρ_{fc}	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Coefficients of Utilization(CU)														
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00														
1.0	1.05	1.01	.98	1.03	.99	.96	.99	.96	.93	.95	.92	.90	.91	.89	.88	.86														
2.0	.92	.86	.80	.90	.84	.79	.87	.82	.77	.83	.79	.76	.80	.77	.74	.72														
3.0	.81	.73	.67	.79	.72	.66	.76	.70	.65	.74	.68	.64	.71	.67	.63	.61														
4.0	.72	.63	.57	.70	.62	.56	.68	.61	.55	.66	.60	.55	.63	.58	.54	.52														
5.0	.64	.55	.49	.63	.55	.48	.61	.54	.48	.59	.52	.47	.57	.51	.47	.45														
6.0	.58	.49	.42	.57	.48	.42	.55	.47	.42	.53	.47	.42	.52	.46	.41	.39														
7.0	.52	.44	.37	.51	.43	.37	.50	.42	.37	.48	.42	.37	.47	.41	.37	.35														
8.0	.48	.39	.33	.47	.39	.33	.46	.38	.33	.44	.38	.33	.43	.37	.33	.31														
9.0	.44	.36	.30	.43	.35	.30	.42	.35	.30	.41	.34	.30	.40	.34	.29	.28														
10.0	.40	.32	.27	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.27	.25														



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.284	.162	.051	.277	.158	.050	.264	.151	.048	.252	.145	.047	.241	.140	.045															
2.0	.276	.151	.046	.270	.149	.046	.258	.144	.045	.248	.139	.043	.238	.134	.042															
3.0	.260	.138	.041	.254	.136	.041	.244	.132	.040	.234	.128	.039	.226	.125	.039															
4.0	.242	.126	.037	.237	.124	.037	.228	.121	.036	.220	.118	.036	.212	.115	.035															
5.0	.225	.115	.033	.221	.113	.033	.213	.111	.033	.205	.108	.032	.198	.106	.032															
6.0	.210	.105	.030	.206	.104	.030	.199	.102	.030	.192	.100	.029	.186	.098	.029															
7.0	.196	.097	.027	.193	.096	.027	.186	.094	.027	.180	.092	.027	.174	.091	.027															
8.0	.183	.090	.025	.180	.089	.025	.175	.087	.025	.169	.086	.025	.164	.084	.025															
9.0	.172	.083	.023	.169	.083	.023	.164	.081	.023	.159	.080	.023	.155	.079	.023															
10.0	.162	.078	.022	.160	.077	.022	.155	.076	.021	.151	.075	.021	.146	.074	.021															

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.179	.156	.136	.153	.134	.117	.104	.092	.081	.060	.053	.047	.019	.017	.015	
2.0	.170	.132	.100	.146	.114	.086	.100	.079	.060	.058	.046	.035	.018	.015	.012	
3.0	.162	.114	.076	.139	.099	.066	.096	.068	.046	.055	.040	.027	.018	.013	.009	
4.0	.155	.101	.059	.133	.087	.052	.092	.061	.036	.053	.036	.021	.017	.012	.007	
5.0	.148	.090	.048	.127	.078	.042	.087	.055	.029	.051	.032	.017	.016	.010	.006	
6.0	.141	.082	.040	.121	.071	.035	.084	.050	.024	.048	.029	.015	.016	.010	.005	
7.0	.134	.075	.034	.116	.065	.029	.080	.046	.021	.046	.027	.012	.015	.009	.004	
8.0	.128	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.042	.023	.009	.014	.008	.003	
10.0	.116	.060	.023	.100	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	17.4	18.9	17.7	19.1	19.3	17.5	19.0	17.7	19.2	19.4
3H	18.9	20.3	19.2	20.5	20.7	18.8	20.2	19.1	20.4	20.7
4H	19.4	20.7	19.8	21.0	21.3	18.7	20.0	19.0	20.3	20.5
6H	19.8	21.0	20.1	21.2	21.5	18.6	19.8	18.9	20.1	20.4
8H	19.8	21.0	20.1	21.3	21.5	18.6	19.7	18.9	20.0	20.3
12H	19.8	20.9	20.1	21.2	21.5	18.5	19.6	18.9	19.9	20.2
4H 2H	18.0	19.3	18.4	19.6	19.9	18.1	19.4	18.4	19.6	19.9
3H	19.7	20.8	20.0	21.1	21.4	19.6	20.7	19.9	21.0	21.3
4H	20.4	21.4	20.7	21.7	22.0	19.5	20.5	19.9	20.8	21.2
6H	20.8	21.7	21.2	22.0	22.4	19.4	20.3	19.8	20.7	21.0
8H	20.8	21.7	21.3	22.1	22.4	19.4	20.2	19.8	20.6	21.0
12H	20.9	21.6	21.3	22.0	22.4	19.3	20.1	19.7	20.5	20.9
8H 4H	20.5	21.3	20.9	21.7	22.1	19.6	20.5	20.1	20.9	21.2
6H	21.0	21.7	21.4	22.1	22.5	19.6	20.3	20.0	20.7	21.1
8H	21.1	21.7	21.5	22.1	22.6	19.5	20.1	20.0	20.6	21.0
12H	21.1	21.6	21.6	22.1	22.6	19.5	20.0	20.0	20.5	20.9
12H 4H	20.5	21.2	20.9	21.6	22.0	19.6	20.4	20.1	20.8	21.2
6H	20.9	21.6	21.4	22.0	22.4	19.5	20.2	20.0	20.6	21.0
8H	21.1	21.6	21.5	22.0	22.5	19.5	20.0	20.0	20.5	21.0
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.4				
1.5H	+ 0.2 / - 0.5					+ 0.4 / - 0.7				
2.0H	+ 0.3 / - 0.6					+ 0.6 / - 1.3				

CIE Pub.117, 2612 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 3.3$)
Area: 0.2444 m²

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	58	47	40	56	46	40	33
0.80	69	57	50	68	57	50	66	56	49	43
1.00	77	66	59	76	66	59	74	67	58	52
1.25	84	74	67	83	74	67	80	72	66	59
1.50	89	80	73	88	79	73	85	77	72	64
2.00	96	88	82	95	87	81	91	85	80	72
2.50	100	93	87	98	91	86	94	89	84	76
3.00	103	97	92	101	96	91	97	93	89	80
4.00	107	102	98	105	100	96	101	97	94	85
5.00	110	105	102	107	103	100	103	100	97	88
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2025-01-20

$V(B)$ Range:-70 - 70DEG
 $V(B)$ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
 Humidity:65.0%
 Test Distance:8.800m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	3286
L_0~180 (75) av	2805
L_0~180 (85) av	1147
L_90~270 (65) av	3288
L_90~270 (75) av	0
L_90~270 (85) av	0
L_45 (65) av	3275
L_45 (75) av	2834
L_45 (85) av	0

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2025-01-20

V(B) Range:-70 - 70DEG
 V(B) Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
 Humidity:65.0%
 Test Distance:8.800m [K=1.0000]
 Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.07V I:0.3287A P:38.910W PF:0.9860 Freq:59.98Hz Lamp Flux:2612.14x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3000K
MFR.:	SUR.: 0.558	Shielding Angle:

Table--4

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

```
V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:
```