


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 73.15 lm/W
MODEL	EGRF2440LAJUDWH_3500K	I _{max} (cd)	1000.0	S/MH(C0/180)	1.26	
NOMINAL POWER(W)	40	LOR(%)	100.0	S/MH(C90/270)	1.26	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	2750.6	η UP,DN(C0-180)	0.0,50.1	
NOMINAL FLUX(lm)	2750.55	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.9	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	120	η down(%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	983.1	982.2	982.5	981.0	981.3	981.9	982.8	982.4	0- 10	94.58	94.58	3.44,3.44
20	931.4	933.6	934.3	930.9	928.8	930.3	930.8	930.6	10- 20	271.2	365.8	13.3,13.3
30	847.5	851.2	851.4	847.4	844.7	846.2	846.8	845.1	20- 30	411.6	777.3	28.3,28.3
40	735.2	740.3	740.3	736.1	733.0	735.2	735.9	732.8	30- 40	496.9	1274	46.3,46.3
50	597.7	603.0	604.3	601.7	598.0	601.5	600.5	595.8	40- 50	516.7	1791	65.1,65.1
60	439.3	444.8	441.5	445.3	443.1	445.4	437.1	438.1	50- 60	466.5	2257	82.1,82.1
70	267.3	271.1	278.7	275.8	275.3	274.8	273.7	264.5	60- 70	353.2	2611	94.9,94.9
80	102.7	0	0	0	113.5	0	0	0	70- 80	129.9	2741	99.6,99.6
90	0.0884	0	0	0	0.0663	0	0	0	80- 90	9.961	2751	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2025-01-20

V(B) Range:-70 - 70DEG
 V(B) Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
 Humidity:65.0%
 Test Distance:8.800m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:




LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1269	0
80	2421	0
75	2876	0
70	3198	3334
65	3429	3486
60	3595	3613
55	3715	3730
50	3804	3847
45	3873	3890

H(β) Range:-90 - 90DEG	V(B) Range:-70 - 70DEG
H(β) Interval: 1.0DEG	V(B) Interval: 2.0DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Temperature:25.3DEG	Humidity:65.0%
Operators:	Test Distance:8.800m [K=1.0000]
Test Date:2025-01-20	Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
p _{fc}	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Coefficients of Utilization(CU)														
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00														
1.0	1.05	1.01	.98	1.03	.99	.96	.99	.96	.93	.95	.92	.90	.91	.89	.88	.86														
2.0	.92	.86	.80	.90	.84	.79	.87	.82	.77	.83	.79	.76	.80	.77	.74	.72														
3.0	.81	.73	.67	.79	.72	.66	.76	.70	.65	.74	.68	.64	.71	.67	.63	.61														
4.0	.72	.63	.57	.70	.62	.56	.68	.61	.55	.66	.60	.55	.63	.58	.54	.52														
5.0	.64	.55	.49	.63	.55	.48	.61	.54	.48	.59	.52	.47	.57	.51	.47	.45														
6.0	.58	.49	.42	.57	.48	.42	.55	.47	.42	.53	.47	.42	.52	.46	.41	.39														
7.0	.52	.44	.37	.51	.43	.37	.50	.42	.37	.48	.42	.37	.47	.41	.37	.35														
8.0	.48	.39	.33	.47	.39	.33	.46	.38	.33	.44	.38	.33	.43	.37	.33	.31														
9.0	.44	.36	.30	.43	.35	.30	.42	.35	.30	.41	.34	.30	.40	.34	.29	.28														
10.0	.40	.32	.27	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.27	.25														



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.: 3500K	
MFR.:		SUR.: 0.558		Shielding Angle:	

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.284	.162	.051	.277	.158	.050	.264	.152	.048	.252	.145	.047	.241	.140	.045															
2.0	.276	.151	.046	.270	.149	.046	.258	.144	.045	.248	.139	.043	.238	.135	.042															
3.0	.260	.138	.041	.254	.136	.041	.244	.132	.040	.235	.128	.039	.226	.125	.039															
4.0	.242	.126	.037	.237	.124	.037	.228	.121	.036	.220	.118	.036	.212	.115	.035															
5.0	.225	.115	.033	.221	.113	.033	.213	.111	.033	.205	.108	.032	.198	.106	.032															
6.0	.210	.105	.030	.206	.104	.030	.199	.102	.030	.192	.100	.029	.186	.098	.029															
7.0	.196	.097	.027	.193	.096	.027	.186	.094	.027	.180	.092	.027	.174	.091	.027															
8.0	.183	.090	.025	.180	.089	.025	.175	.087	.025	.169	.086	.025	.164	.084	.025															
9.0	.172	.083	.023	.169	.083	.023	.164	.081	.023	.159	.080	.023	.155	.079	.023															
10.0	.162	.078	.022	.160	.077	.022	.155	.076	.021	.151	.075	.021	.146	.074	.021															

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.179	.156	.136	.153	.134	.117	.104	.092	.081	.060	.053	.047	.019	.017	.015	
2.0	.170	.132	.100	.146	.114	.086	.100	.079	.060	.058	.046	.035	.018	.015	.012	
3.0	.162	.114	.076	.139	.099	.066	.096	.068	.046	.055	.040	.027	.018	.013	.009	
4.0	.155	.101	.059	.133	.087	.052	.092	.061	.036	.053	.036	.021	.017	.012	.007	
5.0	.148	.090	.048	.127	.078	.042	.087	.055	.029	.051	.032	.017	.016	.010	.006	
6.0	.141	.082	.040	.121	.071	.035	.084	.050	.024	.048	.029	.015	.016	.010	.005	
7.0	.134	.075	.034	.116	.065	.029	.080	.046	.021	.046	.027	.012	.015	.009	.004	
8.0	.128	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.042	.023	.009	.014	.008	.003	
10.0	.116	.060	.023	.100	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	17.6	19.1	17.9	19.3	19.5	17.6	19.1	17.9	19.3	19.5
3H	19.1	20.4	19.4	20.7	20.9	19.0	20.4	19.3	20.6	20.8
4H	19.6	20.9	19.9	21.2	21.4	18.9	20.2	19.2	20.4	20.7
6H	19.9	21.1	20.3	21.4	21.7	18.8	20.0	19.1	20.3	20.5
8H	20.0	21.1	20.3	21.4	21.7	18.7	19.9	19.1	20.2	20.5
12H	20.0	21.1	20.3	21.4	21.7	18.7	19.8	19.0	20.1	20.4
4H 2H	18.2	19.5	18.5	19.8	20.0	18.2	19.5	18.5	19.8	20.0
3H	19.9	21.0	20.2	21.3	21.6	19.8	20.9	20.1	21.2	21.5
4H	20.5	21.6	20.9	21.9	22.2	19.7	20.7	20.0	21.0	21.3
6H	20.9	21.8	21.3	22.2	22.6	19.6	20.5	20.0	20.8	21.2
8H	21.0	21.9	21.4	22.2	22.6	19.5	20.4	19.9	20.7	21.1
12H	21.0	21.8	21.4	22.2	22.6	19.5	20.3	19.9	20.6	21.0
8H 4H	20.7	21.5	21.1	21.9	22.3	19.8	20.7	20.2	21.0	21.4
6H	21.2	21.9	21.6	22.3	22.7	19.7	20.4	20.2	20.8	21.2
8H	21.3	21.9	21.7	22.3	22.7	19.7	20.3	20.1	20.7	21.2
12H	21.3	21.8	21.8	22.3	22.7	19.6	20.2	20.1	20.6	21.1
12H 4H	20.6	21.4	21.1	21.8	22.2	19.8	20.6	20.2	20.9	21.3
6H	21.1	21.7	21.6	22.2	22.6	19.7	20.3	20.2	20.7	21.2
8H	21.2	21.7	21.7	22.2	22.7	19.7	20.2	20.1	20.6	21.1
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.4				
1.5H	+ 0.2 / - 0.5					+ 0.4 / - 0.7				
2.0H	+ 0.3 / - 0.6					+ 0.6 / - 1.3				

CIE Pub.117, 2751 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 3.5$)
Area: 0.2444 m²

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	58	47	40	56	46	40	33
0.80	69	57	50	68	57	50	66	56	49	43
1.00	77	66	59	76	66	59	74	67	58	52
1.25	84	74	67	83	74	67	80	72	66	59
1.50	89	80	73	88	79	73	85	77	72	64
2.00	96	88	82	95	87	81	91	85	80	72
2.50	100	93	87	98	91	86	94	89	84	76
3.00	103	97	92	101	96	91	97	93	89	80
4.00	107	102	98	105	100	96	101	97	94	85
5.00	110	105	102	107	103	100	103	100	97	88
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2025-01-20

$V(B)$ Range:-70 - 70DEG
 $V(B)$ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
 Humidity:65.0%
 Test Distance:8.800m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:



H(β) Range:-90 - 90DEG	V(B) Range:-70 - 70DEG
H(β) Interval: 1.0DEG	V(B) Interval: 2.0DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Temperature:25.3DEG	Humidity:65.0%
Operators:	Test Distance:8.800m [K=1.0000]
Test Date:2025-01-20	Remarks:

LED Avg.L Report

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	3458
L_0~180 (75) av	2953
L_0~180 (85) av	1208
L_90~270 (65) av	3464
L_90~270 (75) av	0
L_90~270 (85) av	0
L_45 (65) av	3449
L_45 (75) av	2987
L_45 (85) av	0

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:

Table--2

UNIT: cd

[illegible]

```
H( $\beta$ ) Range:-90 - 90DEG
H( $\beta$ ) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20
```

```
V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.07V I:0.3178A P:37.602W PF:0.9856 Freq:59.98Hz Lamp Flux:2750.55x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 3500K
MFR.:	SUR.: 0.558	Shielding Angle:

Table--3

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-01-20

V(B) Range:-70 - 70DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.454
Humidity:65.0%
Test Distance:8.800m [K=1.0000]
Remarks:

