

# Ashland LED Flush Mount ALDF Series

## **Features**

Contemporary shallow flush mount with a linen fabric shade. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

#### Construction

Fabric linen shade with flat white diffuser. Back pan is made from 22-gauge stamped steel and painted in lighting grade white. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

## **Finish**

Grey linen fabric shade.

#### Diffuser

Diffuser is made of 0.100" thick standard white acrylic.

#### **Electrical**

Input 120VAC / 60 Hz.
Compatible with TRIAC and ELV dimmers.

#### LED

Integrated LED modules capable of producing: 22W = 1800 source lumens, 1200 delivered lumens 33W = 2500 source lumens, 1950 delivered lumens 46W = 3200 source lumens, 2500 delivered lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

## Certification

All fixtures are cETLus listed for indoor damp locations Title 24/JA8 Compliant

## Options for 15" and 20" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

#### Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.















## **Ordering Information:**

		Source	Delivered			
Grey	LED	Lumens	Lumens	Adjustable CCT	DIA.	D
ALDF1318LAJD1GY	22W	1800	1200	3000K/3500K/4000K	12-1/2"	3-1/2"
ALDF1525LAJD1GY	33W	2500	1950	3000K/3500K/4000K	15"	3-1/2"
ALDF2032LAJD1GY	46W	3200	2500	3000K/3500K/4000K	20"	4-1/2"