



Anton LED Flush Mount ANF Series

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Features

This modern single drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade. White bottom acrylic diffuser disperses the light. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).



Construction

The canopy is made of 22-gauge cold rolled steel. The LED pan is white painted. The acrylic diffuser is supported by the inner shade. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Stamped metal components are paintable white baked gloss enamel.

Diffuser

Utilizing Lumafuse™ laminated fabric to acrylic.
Jute and Linen White. Matte white acrylic bottom lay-in diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
18W = 1400 source lumens
30W = 2400 source lumens
42W = 3200 source lumens
60W = 5400 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
*Title 24/JA8 Compliant (Linen White ONLY)

Options (excludes 12" models)

Emergency Battery Back-Up (add -BB to the end of the model number)
Motion Sensor (add -MS to the end of the model number)
Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

Ordering Information:


Jute	Linen White*	LED	Source Lumens	Adjustable CCT	DIA.	D
ANF1214LAJUD-JT	ANF1214LAJUD-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"
ANF1524LAJUD-JT	ANF1524LAJUD-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"
ANF1932LAJUD-JT	ANF1932LAJUD-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"
ANF2432LAJUD-JT	ANF2432LAJUD-LW	42W	3200	3000K/3500K/4000K	24"	7-1/2"
ANF3044LAJUD-JT	ANF3044LAJUD-LW	60W	5400	3000K/3500K/4000K	30"	9-1/2"



Jute



Linen White



BATTERY BACKUP



FLUSH MOUNT