



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Anton LED Pendant ANP Series

Features

This modern double layer drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Includes (2) 6" and (2) 12" adjustable stems with swivel on canopy for 60 deg sloped ceiling.

Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel finish.

Diffuser

Utilizing Lumafuse™ laminated fabric to acrylic in Jute or Linen White. Matte white acrylic bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
18W = 1400 source lumens
30W = 2400 source lumens
42W = 3200 source lumens
60W = 5400 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs., 90 CRI

Certification

All fixtures are cETLus listed for indoor damp locations.
*Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel/Jute	Satin Nickel/ Linen White*	LED	Source Lumens	Adjustable CCT	DIA.	H
ANP1214LAJUDSN-JT	ANP1214LAJUDSN-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"
ANP1524LAJUDSN-JT	ANP1524LAJUDSN-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"
ANP1932LAJUDSN-JT	ANP1932LAJUDSN-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"
ANP2432L5AJUDSN-JT	ANP2432L5AJUDSN-LW	42W	3200	3000K/3500K/4000K	24"	7-1/2"
ANP3044L5AJUDSN-JT	ANP3044L5AJUDSN-LW	60W	5400	3000K/3500K/4000K	30"	9-1/2"

Black/Jute	Black/Linen White*	LED	Source Lumens	Adjustable CCT	DIA.	H
ANP1214LAJUDBK-JT	ANP1214LAJUDBK-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"
ANP1524LAJUDBK-JT	ANP1524LAJUDBK-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"
ANP1932LAJUDBK-JT	ANP1932LAJUDBK-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"
ANP2432L5AJUDBK-JT	ANP2432L5AJUDBK-LW	42W	3200	3000K/3500K/4000K	24"	7-1/2"
ANP3044L5AJUDBK-JT	ANP3044L5AJUDBK-LW	60W	5400	3000K/3500K/4000K	30"	9-1/2"



SN-LW



SN-JT

