

## Apex LED Flush Mount APF Series

## **Features**

Solid wood with accent detail. Features Lumafuse<sup>™</sup> laminated fabric/acrylic shade. White bottom acrylic diffuser disperses the light. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

### Construction

Special laminated fabric on acrylic material with solid wood trim and white bottom diffuser. Back pan is made from 22-gauge stamped steel and painted in lighting grade white. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

#### Finish

Solid wood accent available in espresso or weathered grey finish.

#### Diffuser

Utilizing Lumafuse™ laminated fabric to acrylic. Linen white and Jute. Matte white acrylic bottom diffuser.

#### Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

#### LED

Integrated LED modules capable of producing: 18W = 1400 source lumens 30W = 2400 source lumens 42W = 3200 source lumens 60W = 5400 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50.000 Hrs., 90 CRI.

## Certification

All fixtures are cETLus listed for indoor damp locations. \*Title 24/JA8 Compliant (Linen White ONLY)

## **Options (excludes 14" models)**

Emergency Battery Back-Up (add -BB to the end of the model number) Motion Sensor (add -MS to the end of the model number) Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)

#### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

## Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

APF3044L5AJUDES-LW APF3044L5AJUDWG-LW 60W

# **Ordering Information:**

			Source				
Espresso/Jute	Weathered Grey/Jute	LED	Lumens	Adjustable CCT	DIA.	D	
APF1214LAJUDES-JT	APF1214LAJUDWG-JT	18W	1400	3000K/3500K/4000K	14-1/4″	4-1/4"	
APF1524LAJUDES-JT	APF1524LAJUDWG-JT	30W	2400	3000K/3500K/4000K	17″	4-1/4"	
APF1932LAJUDES-JT	APF1932LAJUDWG-JT	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"	
APF2432L5AJUDES-JT	APF2432L5AJUDWG-JT	42W	3200	3000K/3500K/4000K	27-1/4″	6"	
APF3044L5AJUDES-JT	APF3044L5AJUDWG-JT	60W	5400	3000K/3500K/4000K	33-3/8"	7-1/4″	
	Weathered Grey/		Source				
Espresso/Linen White*	Linen White*	LED	Lumens	Adjustable CCT	DIA.	D	
APF1214LAJUDES-LW	APF1214LAJUDWG-LW	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"	
APF1524LAJUDES-LW	APF1524LAJUDWG-LW	30W	2400	3000K/3500K/4000K	17″	4-1/4"	
APF1932LAJUDES-LW	APF1932LAJUDWG-LW	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"	
ADE2/1321 5A ILIDES-LW	APE2/32L5A ILIDWG-LW	12\1/	3200	3000K/3500K/4000K	27-1///"	6"	


LOCATION DATE
PREPARED
BY
QUANTITY
COMMENTS
CATALOG
NUMBER
DATE
DATE
FIXTURE TYPE








Espresso/Jute





BATTERY BACKUP

5400

3000K/3500K/4000K 33-3/8" 7-1/4"