

Apex LED Pendant APP Series

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE

Features

This modern double layer drum design provides a dramatic look and features. Lumafuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Includes (2) 6" and (2) 12" adjustable stems with swivel on canopy for 60 deg sloped ceiling.







Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Espresso or Weathered Grey solid wood accents. Satin Nickel canopy and stems.

Diffuser

LumaFuse™ laminated fabric/acrylic front shade in Jute or Linen White. White bottom acrylic diffuser

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:

18W = 1400 source lumens

30W = 2400 source lumens

42W = 3200 source lumens

60W = 5400 source lumens

Adjustable Choice 3000K, 3500K, 4000K (CCT).

Rated for 50,000 Hrs, 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. *Title 24/JA8 Compliant


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date-of-purchase.

Specifications and dimensions subject to change without notice.







Ordering Information:

			Source			
Espresso/Jute	Weathered Grey/Jute	LED	Lumens	Adjustable CCT	DIA.	Н
APP1214LAJUDES-JT	APP1214LAJUDWG-JT	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"
APP1524LAJUDES-JT	APP1524LAJUDWG-JT	30W	2400	3000K/3500K/4000K	17"	4-1/4"
APP1932LAJUDES-JT	APP1932LAJUDWG-JT	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"
APP2432L5AJUDES-JT	APP2432L5AJUDWG-JT	42W	3200	3000K/3500K/4000K	27-1/4"	6"
APP3044L5AJUDES-JT	APP3044L5AJUDWG-JT	60W	5400	3000K/3500K/4000K	33-3/8"	7-1/4"

	Weathered Grey/		Source			
Espresso/Linen White*	Linen White*	LED	Lumens	Adjustable CCT	DIA.	Н
APP1214LAJUDES-LW	APP1214LAJUDWG-LW	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"
APP1524LAJUDES-LW	APP1524LAJUDWG-LW	30W	2400	3000K/3500K/4000K	17"	4-1/4"
APP1932LAJUDES-LW	APP1932LAJUDWG-LW	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"
APP2432L5AJUDES-LW	APP2432L5AJUDWG-LW	42W	3200	3000K/3500K/4000K	27-1/4"	6"
APP3044L5AJUDES-LW	APP3044L5AJUDWG-LW	60W	5400	3000K/3500K/4000K	33-3/8"	7-1/4"