



Arlo LED Vanity ARLV Series

Features

LED contemporary style. Satin nickel finish with frosted acrylic diffusers provide a modern geometric design to this vanity. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All exposed metal is finished in satin nickel.

Diffuser

Diffusers are made from a thick frosted acrylic.

Electrical

Input 120V / 60Hz for D1 model and 120-277VAC / 60Hz for MV model. Compatible with residential (TRIAC/ELV) dimming only at 120 VAC (D1).

LED

Integrated LED modules capable of producing:
25" - 30W, 1800 source lumens
33" - 40W, 2400 source lumens
3500K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for damp locations.
ADA
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	CCT	L	H	D
ARLV250418L35D1SN (3-Light)	30W	1800	3500K	25"	4"	3-3/4"
ARLV250418L35MVSN (3-Light)	30W	1800	3500K	25"	4"	3-3/4"
ARLV330424L35D1SN (4-Light)	40W	2400	3500K	33"	4"	3-3/4"
ARLV330424L35MVSN (4-Light)	40W	2400	3500K	33"	4"	3-3/4"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

