# $\wedge F \times$

## Atlas Flush Mount ATLF Series

## Features

This low profile, clean appearance, surface mounted wrap provides a wide distribution of light. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

#### Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes are included. Power supply connections can be made inside the fixture wire way or in a junction box (not included).

#### Finish

Satin Nickel finish.

#### Diffuser

White diffuser is made of engineered LED acrylic material.

#### Electrical

Input 120 VAC, 60 Hz. The LED driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

## LED

Integrated LED modules capable of producing: 18.5W = 1800 source lumens, 1100 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

#### Certification

cETLus listed for damp locations. Title 24/JA8 Compliant Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements

#### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

# **Ordering Information:**

		Source	Delivered	d k			_
				ССТ			
ATLF12121100L30D1SN	18.5W	1800	1100	3000K	15″	15″	2″







Satin Nickel

