



Atlas LED Linear ATL Series

Features

This low profile, clean appearance, surface mounted wrap provides a wide distribution of light. It can be used in various applications including offices, corridors, garages, kitchens and public spaces. Fixture mounts to a standard junction box (not included).

Construction

Housing is die-formed of 22-gauge steel. Power supply connections must be made inside the fixture wire way or inside a junction box (not included).

Finish

Satin nickel or oil-rubbed bronze frame finish.

Diffuser

White diffuser is made of engineered LED acrylic material.

Electrical

Input 120 VAC / 60 Hz.
Compatible with TRIAC or ELV dimmers.

LED

Integrated LED modules capable of producing:
39W, 3200 source lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification


cETLus listed for indoor damp locations.
ENERGY STAR® qualified
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



Ordering Information:

Satin Nickel	Oil-Rubbed Bronze	LED	Source Lumens	CCT	L	W	H
ATL12483200L30D1SN	ATL12483200L30D1RB	39W	3200	3000K	50-3/8"	15"	2"