# AFX

## Avenue LED Outdoor Sconce
## AUW Series

### Features

This outdoor LED light is ideal for security and general lighting.
Decorative metal accents. 3 in 1 color temperature adjustable option.
Provides lighting in indoor or outdoor residential, commercial,
and hospitality applications. Meets ADA requirements.
Fixture mounts to a standard junction box (not included).

### Construction

Die-cast aluminum construction. Standard mounting holes and
hardware are included. Power supply connections must be made
inside a junction box (not included).

### Finish

Available in Textured Grey or Textured Bronze powder coat finish.

### Diffuser

Diffuser is .100" thick matte white acrylic.

### Electrical

Input 120-277 VAC / 60 Hz.
Compatible with 0-10V dimmers (36" ONLY*)
Minimum starting temp -4° F/-20° C

### LED

Integrated LED modules capable of producing:
24W = 2500 source lumens, 1438 delivered lumens
28W = 3200 source lumens, 1647 delivered lumens
42W = 4300 source lumens, 2250 delivered lumens
3000K (12" and 18") or Adjustable Choice 3000K, 3500K, 4000K CCT (36" ONLY*).
Rated for 50,000 Hrs. 90 CRI.

### Certification

All fixtures are cETLus listed for outoor wet locations.
ADA
Title 24/JA8 Compliant

### Option (Consult Factory)

Integrated dusk-to-dawn photocell, add -PC to the end of part number

### Warranty

Limited warranty: This fixture is free from
defects in materials and workmanship for
a period of 5 years from date of purchase.

**Specifications and dimensions
subject to change without notice.**

**Limited Quantities Remain.
Consult Factory.**



TZ 12"

TZ 18"

BZ 36"

## Ordering Information:

| Textured Grey | Textured Bronze | LED | Source Lumens | Delivered Lumens | CCT | H | W | D |
|---|---|---|---|---|---|---|---|---|
| AUW6122500L30MVTG | AUW6122500L30MVBZ | 24W | 2500 | 1438 | 3000K | 12" | 5-1/2" | 3-1/2" |
| AUW7183200L30MVTG | AUW7183200L30MVBZ | 28W | 3200 | 1647 | 3000K | 18" | 7" | 3-1/2" |

| Textured Grey | Textured Bronze | LED | Source Lumens | Delivered Lumens | Adjustable CCT | H | W | D |
|---|---|---|---|---|---|---|---|---|
| AUW103643LAJD2TG* | AUW103643LAJD2BZ* | 42W | 4300 | 2250 | 3000K/3500K/4000K | 36" | 8" | 4" |