



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Avalon LED Striplight AVNL Series

Features

This low profile, clean appearance, surface mounted striplight provides high light levels with a white acrylic diffuser. Available in 2 ft., 4 ft., and 8 ft. lengths. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to a standard junction box (not included) on a ceiling or wall.



Construction

Housing is die-formed of 22-gauge steel. Power supply connections must be made inside the junction box (not included).

Finish

Pre-finished white steel housing.

Diffuser

White acrylic.

Electrical

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. 0-10 V dimming.

LED

Integrated LED modules capable of producing:

- 25W = 2500 delivered lumens
- 43W = 4000 delivered lumens
- 76W = 7900 delivered lumens
- Adjustable CCT - 3000K/4000K/5000K
- Rated for 50,000 hours, 90 CRI.

Options

- Emergency Battery Back-Up (-BB)
- Motion Sensor (-MS)
- Emergency Battery Back-Up with Motion Sensor (-MSBB)

Certification

cETLus listed for indoor damp locations.


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.



Ordering Information:

White	LED	Delivered Lumens	Adjustable CCT	L	W	D
AVNL2430LAJD2WH	25W	2500	3000K/4000K/5000K	24"	2-1/4"	2-3/4"
AVNL4848LAJD2WH	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL4848LAJD2WH-BB	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL4848LAJD2WH-MS	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL4848LAJD2WH-MSBB	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL9685LAJD2WH	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"
AVNL9685LAJD2WH-BB	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"
AVNL9685LAJD2WH-MS	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"
AVNL9685LAJD2WH-MSBB	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"