



## Bilbao LED Flush Mount BBF Series

### Features

Geometric banded ceiling mount fixture is available in two diameters and can be used in various applications including corridors, baths and public spaces. This product offers a cam latch retention assembly for ceiling and wall mounting. Fixture mounts to standard junction box (not included).

### Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Glass frame assembly consists of .06 aluminum-extruded bands that are screwed to vertical supports and glass diffuser is retained with a spun aluminum frame. Power supply connections must be made inside a junction box (not included).

### Finish

Back plate is finished in lighting grade white baked gloss enamel paint. Frame assembly consists of extruded satin aluminum bands with clear lacquer topcoat.

### Diffuser

Glass diffuser is .125" thick hand-blown frosted white glass.

### Electrical

This unit is direct wired with a constant current low voltage electronic LED driver powered at 120 VAC/60 Hz. (D1) The driver is dimmable down to 10% of full scale with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer or choose a 120-277V (D2) driver dimmable 0-10V DC.

### Lamping

Fixture includes LED modules capable of producing:  
13" - 15W - 1400 source lumens  
16" - 24W - 2400 source lumens  
3000K (CCT), 50,000 hr. LED life, 90 CRI

### Certification

All fixtures are cETLus listed for damp locations.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions**  
subject to change without notice.

## Ordering Information:

Satin Aluminum	LED	Source Lumens	DIA.	D
BBF131400L30D1SA	15W	1400	13-1/2"	4-1/2"
BBF131400L30D2SA	15W	1400	13-1/2"	4-1/2"
BBF162400L30D1SA	24W	2400	16-1/2"	4-1/2"
BBF162400L30D2SA	24W	2400	16-1/2"	4-1/2"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

