

Boon Drum LED Pendant BONP Series

Features

Decorative cut metal cylinder pendant is suspended with a 9 ft. adjustable cable. Product can be used over receptions desks, restaurants, and in public spaces. Canopy mounts to a standard junction box (not included).

Construction

Stamped metal with die-cut. The canopy fits over a standard junction box. Power supply connections must be made inside the junction box (not included).

Finish

Painted white or black metal finish.

Diffuser

White acrylic edge-lit light panel.

Electrical

Input 120 VAC / 60HZ.
Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 36W = 3000 source lumens, 1918 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

			Source	Delivered			
Black	White	LED	Lumens	Lumens	CCT	DIA.	Н
BOND2032L30D1BK	BOND20321 30D1WH	36\\\/	3000	1918	3000K	20"	8-1/2"

LOCATION		DATE
PREPARED		
BY		QUANTITY
COMMENTS		
		FIXTURE TYPE
CATALOG	_	
NUMBER		



Limited Quantities Remain. Consult Factory.



