



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Boon LED Pendant BONP Series

Features

Decorative cut metal cylinder pendant is suspended with an 9 ft. adjustable cord. Product can be used over receptions desks, restaurants, and in public spaces. Canopy mounts to a standard junction box (not included).

Construction

Stamped metal with die-cut. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Painted white or black metal finish.

Diffuser

White acrylic.

Electrical

Input 120-277 VAC, 60 Hz LED.
LED driver is 0-10V DC dimmable.

LED

Integrated LED module capable of producing:
12W = 780 source lumens, 300 delivered lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Black	White	LED	Source Lumens	Delivered Lumens	CCT	DIA.	H
BONP0407L30D2BK	BONP0407L30D2WH	12W	780	300	3000K	3-1/2"	12"

**Limited Quantities Remain.
Consult Factory.**

