



Brink LED Sconce BRKS Series

Features

Contemporary wall sconce. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture can be mounted horizontally or vertically. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in black or gold.

Diffuser

Back lit illumination.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

Lamping

Integrated LED modules capable of producing:
18W = 1270 delivered lumens
25W = 1970 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
Title 24/JA8 compliant
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Black	Gold	LED	Delivered		H	W	D
			Lumens	Adjustable CCT			
BRKS0424LAJUDBK	BRKS0424LAJUDGD	18W	1270	2700K/3000K/3500K/4000K/5000K	24"	3-1/2"	2-3/4"
BRKS0636LAJUDBK	BRKS0636LAJUDGD	25W	1970	2700K/3000K/3500K/4000K/5000K	36"	4-1/2"	3-7/8"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



BK



GD

