



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Brio Outdoor Sconce BRW Series

Features

Half cylinder outdoor wet location wall mount sconce offers high quality decorative extruded aluminum bands. Closed clear acrylic top and open bottom allow for wall wash effect. Can be ordered with photocell option (PC). Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 18-gauge aluminum. Decorative bands are .060 extruded aluminum with an apparent thickness of .100" that are screwed to a 22-gauge back plate. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Back plate and bands are finished in satin nickel and oil-rubbed bronze with a clear lacquer topcoat.

Diffuser

Diffuser is .100" thick matte white extruded acrylic that installs from the top and slides into position. Allow 18" from top of fixture to any obstruction to clear lens installation.

Electrical

UL listed electronic high power factor ballast for 120-277V universal 50/60 Hz AC. Minimum starting temperature 0 degree F.

Lamping

For use with 2/18 watt compact fluorescent 4-pin quad lamps; not included.


Certification

All fixtures are cULus listed for wet locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 2 years from date of purchase.

Specifications and dimensions
subject to change without notice.



MC - Mounting Center

Ordering Information:

Satin Nickel	Oil-Rubbed Bronze	Qty.	Lamp	H	W	D
BRW218SNMV	BRW218RBMV	2	18W CFQ 4-Pin	18"	7-1/4"	4-5/8"
BRW218SNEC-PC	BRW218RBEC-PC	2	18W CFQ 4-Pin	18"	7-1/4"	4-5/8"