



## Cirrus LED Flush Mount C2F Series

### Features

A round floating cloud style with a white diffuser.  
Ideal use in kitchens, hallways, and anywhere general lighting is needed.  
Provides lighting in residential, commercial and hospitality applications.  
Fixture mounts to standard junction box (not included).

### Emergency Back-Up (Optional '-BB')

- 90 minute run-time
- 7.4V 2500 mAh Lithium Ion Battery
- 8 watts

### Construction

A 22-gauge steel housing made by stamping process and painted in lighting grade white to provide long lasting finish with 3 side white screws to hold molded diffuser. Standard mounting holes and hardware included.  
Power supply connections must be made inside a junction box (not included).

### Finish

White finish.

### Diffuser

0.070" thick smooth white acrylic.

### Electrical

Input 120VAC / 60 Hz.  
Compatible with TRIAC and ELV dimmers.

### LED

Integrated LED modules capable of producing:  
17W = 1258 delivered lumens  
27W = 1600 delivered lumens  
35W = 2236 delivered lumens  
Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).  
Rated for 50,000 Hrs. 90 CRI.

### Certification

All fixtures are cETLus listed for indoor damp locations.  
T24-JA8 Compliant.  
Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

### Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



FLUSH MOUNT



BATTERY BACKUP

## Ordering Information:

White	LED	Delivered Lumens	Adjustable CCT	DIA.	D
C2F111600L5AJD1	17W	1258	2700K/3000K/3500K/4000K/5000K	11"	3"
C2F142400L5AJD1	27W	1600	2700K/3000K/3500K/4000K/5000K	14"	3"
C2F142400L5AJD1-BB	27W	1600	2700K/3000K/3500K/4000K/5000K	14"	3"
C2F193100L5AJD1	35W	2236	2700K/3000K/3500K/4000K/5000K	19"	3"
C2F193100L5AJD1-BB	35W	2236	2700K/3000K/3500K/4000K/5000K	19"	3"