



Carlisle LED Flush Mount CAF Series (MV)

Features

Metal trim bands with a white floating diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge steel pan made by stamping process and painted in lighting grade white. A vacuum formed diffuser is secured with decorative dual metal bands. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

Satin Nickel or Oil-Rubbed Bronze** metal trim bands.

Diffuser

0.080" thick vacuum formed smooth white acrylic.

Electrical

Input 120-277 VAC, 60 Hz.

LED

Fixture includes an LED module capable of producing:

12" - 13W = 1200 source lumens

14" - 13W = 1200 source lumens

14" - 27W = 2400 source lumens

18" - 27W = 2900 source lumens

3000K (CCT). Rated for 50,000 Hrs., 80 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements. ENERGY STAR® Qualified*

Options for 14" and 18" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	Oil-Rubbed Bronze**	LED	Source Lumens	CCT	DIA.	D
CAF121200L30MV*	CAF121200L30MVRB	13W	1200	3000K	12"	3-1/2"
CAF141200L30MV	CAF141200L30MVRB	13W	1200	3000K	14"	4"
CAF142400L30MV	CAF142400L30MVRB	27W	2400	3000K	14"	4"
CAF182900L30MV	CAF182900L30MVRB	27W	2900	3000K	18"	3-1/2"

**Special Order - consult factory for MOQ and lead time.

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

