



Carlisle LED Flush Mount - Universal Driver CAF Series

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Features

Metal trim bands with a white floating diffuser. Adjustable output on 14" model. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).



Construction

A 22-gauge steel pan made by stamping process and painted in lighting grade white. A vacuum formed diffuser is secured with decorative dual metal bands. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel metal trim bands.

Diffuser

0.080" thick vacuum formed smooth white acrylic.

Electrical

Input 120-277 VAC / 60 Hz.
0-10V dimming (120-277V), TRIAC/ELV (120V)

LED

Integrated LED modules capable of producing:
12" - 13W = 1200 delivered lumens
14" - 13W/27W = 1180/2360 delivered lumens
18" - 34W = 2930 delivered lumens
24" - 34W = 3250 delivered lumens
Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
Title 24/JA8 Compliant
Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Options for 14", 18" & 24" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

Ordering Information:

Satin Nickel	LED	Delivered Lumens	Adjustable CCT	DIA.	D
CAF12L5AJUDSN	13W	1200	2700K/3000K/3500K/4000K/5000K	12"	3-1/2"
CAF14L5AJUDSN	13W/27W	1180/2360	2700K/3000K/3500K/4000K/5000K	14"	3-1/2"
CAF18L5AJUDSN	34W	2930	2700K/3000K/3500K/4000K/5000K	18"	3-1/2"
CAF24L5AJUDSN	34W	3250	2700K/3000K/3500K/4000K/5000K	24"	5"

