ΛFX

Cortez LED	Semi-Flush
CZF Series	

Features

Semi-flush mount with a shade-in-shade fabric and a white acrylic diffuser. Ideal use for general lighting in indoor residential, commercial, and hospitality applications. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge metal pan made by stamping process surrounded by shade in shade style and recessed from the ceiling with matching canopy finish. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel canopy.

Diffuser

A sheer organza outer shade and a white linen inner shade.

Electrical

Input 120-277 VAC / 60Hz. Compatible with residential (TRIAC/ELV) and commercial (0-10) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 30W = 2400 source lumens 42W = 3200 source lumens 60W = 4400 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions

subject to change without notice.

Ordering Information:

		Source				
Satin Nickel/White	LED	Lumens	Adjustable CCT	DIA.	D	S
CZF1824LAJUDSN-WHWH	30W	2400	3000K/3500K/4000K	18″	7-1/4"	5″
CZF2432LAJUDSN-WHWH	42W	3200	3000K/3500K/4000K	24"	8″	5″
CZF3040LAJUDSN-WHWH	60W	4400	3000K/3500K/4000K	30″	9"	6″







