



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Dexter LED Outdoor Sconce DEXW Series



### Features

This outdoor LED light is ideal for security and general lighting. Choose from up or down light illumination (1-Light) or up and down light illumination (2-Light) with adjustable beam angle. Beam angle - 30deg Min up to 106deg Max. For use in outdoor or indoor residential, commercial, and hospitality applications. Vertical or horizontal mounting. Fixture mounts to a standard junction box (not included).

### Construction

Fabricated aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### Finish

Black, Bronze or White powder coat finish.

### Diffuser

Clear glass diffuser.

### Electrical

Input 120-277 VAC / 60 Hz.  
Minimum starting temp -4° F / -20°C.

### LED

Integrated LED modules capable of producing:  
1-LIGHT - 12W = 1200 source lumens, 537 delivered lumens  
2-LIGHT - 24W = 2400 source lumens, 1025 delivered lumens  
3000K (CCT). Rated for 50,000 Hrs., 80 CRI.

### Certification

All fixtures are cETLus listed for wet locations.  
Title 24/JA8 Compliant (outdoor only).  
ADA

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions  
subject to change without notice.**




BK



WH



BZ



## Ordering Information:

Black	Bronze	White	LED	Source Lumens	Delivered Lumens	CCT	H	W	D
DEXW060612L30MVBK (1-LIGHT)	DEXW060612L30MVBZ (1-LIGHT)	DEXW060612L30MVWH (1-LIGHT)	12W	1200	537	3000K	5-1/2"	5-1/2"	2-1/4"
DEXW060624L30MVBK (2-LIGHT)	DEXW060624L30MVBZ (2-LIGHT)	DEXW060624L30MVWH (2-LIGHT)	24W	2400	1025	3000K	5-1/2"	5-1/2"	2-1/4"