

Edge Round Large LED Surface Mount Disc Light EGRF Series

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	-

5in1 CCT





Features

This ultra low profile design provides a dramatic look and features an edge-lit light panel construction. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed. Indoor use only - Wall or ceiling mount.

Outdoor use only - Covered ceiling mount.

Construction

Edge-lit technology housing is injection molded with steel backplate. Twist and lock bracket.

Mounts to standard junction box (not included).

Power supply connections must be made inside junction box.

Finish

White or Black finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Intergrated LED modules capable of producing: 25W = 2525 delivered lumens 40W = 3375 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

cETLus listed Title 24/JA8 Compliant


Wet location rated for indoor use. Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use). Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.







Ordering Information:

Delivered								
White	Black	LED	Lumens	Adjustable CCT	DIA.	D		
EGRF1625LAJUDWH	EGRF1625LAJUDBK	25W	2525	3000K/4000K/5000K	15-5/8"	15/16"		
EGRF1625LAJUDWH	EGRF1625LAJUDBK	25W	2525	3000K/4000K/5000K	15-5/8"	15/16"		
EGRF2440LAJUDWH	EGRF2440LAJUDBK	40W	3375	3000K/4000K/5000K	23-5/8"	1"		
EGRF2440LAJUDWH	EGRF2440LAJUDBK	40W	3375	3000K/4000K/5000K	23-5/8"	1"		