

Elena Task Lighting ELNU Series

Features

The ELNU series low profile make it ideal for undercabinet lighting in kitchens, study area and displays. A pivoting light bar will allow for direct light in where needed most. Available in 5 different lengths, ranging from 10" to 40" to handle most application requirements.

to francie most application requirements.

LOCATION

COMMENTS

CATALOG NUMBER

- Captive mounting screws
- · Direct wire option through multiple knockouts





DATE

QUANTITY

FIXTURE TYPE



- Pivoting light bar adjustable beam angle Linkable up to 200 Watts
- USB-A and USB-C charging ports
- BX/NM cable connector
- Direct connector (included)
- 5 CCT color changing switch

Construction

Fixture housing is made from extruded aluminum.

Finish

All exposed metal parts are painted Black or White.

Diffuser

White polycarbonate.

Electrical

Input 120V 60 Hz. This product provides a user selectable switch with 5 color choices - 2700K, 3000K, 3500K, 4000K & 5000K CCT respectively. The fixture is dimmable with most standard 2 wire (Triac) wall dimmers or an electronic low voltage dimmer switch (sold separately).

USB-A, USB-C charging ports on 14, 22, 32, 40 inch models ONLY.







LED

Integrated LED type SMT array, non-replaceable arrays use from 5 to 20 Watts and produce from 300 to 1300 lumens. Create 2700K, 3000K, 3500K, 4000K or 5000K color temps. Rated to 50,000 hrs. 90 CRI.


Certification

Fixtures are cETLus listed for indoor damp locations and carry a ETL rating for undercabinet/convertible/linkable mounting. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



ACCESSORIES (ORDER SEPARATELY)

ACCESSORIES	(ONDER SEPARATELT)
XLCC12WH	12" Interconnect cord - White
XLCC12BL	12" Interconnect cod - Black
XLCC24WH	24" Interconnect cord - White
XLCC24BL	24" Interconnect cord - Black
XLCC36WH	36" Interconnect cord - White
XLCC36BL	36" Interconnect cord - Black
XLCC48WH	48" Interconnect cord - White
XLCC48BL	48" Interconnect cord - Black
XLCC72WH	72" Interconnect cord - White
XLCC72BL	72" Interconnect cord - Black
XLCP60WH	60" Cord & Plug - White
XLCP60BL	60" Cord & Plug - Black
XLHBWH	Hardwire Box - White
XLHBBL	Hardwire Box - Black
VI C-Clins	Close Cord Clip with Scrows (4 p

Clear Cord Clip with Screws (4 pieces)
Occupancy sensor

Adjustable Light Bar

Ordering Information:

				Lumens				
Size	Black	White	Туре	3000K	LPW	L	W	D
10 in.	ELNU10BK	ELNU10WH	5W	285	57	10"	2-3/4"	1"
14 in.	ELNU14BK	ELNU14WH	8W	508	63	14"	2-3/4"	1"
22 in.	ELNU22BK	ELNU22WH	12W	805	67	22"	2-3/4"	1"
32 in.	ELNU32BK	ELNU32WH	16W	1094	68	32"	2-3/4"	1"
40 in.	ELNU40BK	ELNU40WH	20W	1341	67	40"	2-3/4"	1"



LCX-OCC