



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Elston LED Outdoor Sconce ELTW Series



Features

Outdoor LED light with integrated photocell for dusk to dawn operations. Ideal use for security and general lighting in outdoor residential, commercial, and hospitality applications. Fixture mounts to a standard junction box (not included).

Construction

Die-cast aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Brushed aluminum or black.

Diffuser

White acrylic diffuser.

Electrical

Built-in photocell

Input 120 VAC / 60 Hz.

Minimum starting temperature -4°F/-20° C

LED

Integrated LED modules capable of producing:

13W = 1050 source lumens, 725 delivered lumens

21W = 1900 source lumens, 1175 delivered lumens

25W = 2250 source lumens, 1625 delivered lumens

Adjustable Choice 3000K, 3500K, 4000K (CCT).

Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for wet locations.

Title 24/JA8 Compliant (outdoor only).

ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions
subject to change without notice.**



Ordering Information:

Brushed Aluminum	Black	LED	Source Lumens	Delivered Lumens	Adjustable CCT	H	W	D
ELTW0710LAJD1BA	ELTW0710LAJD1BK	13W	1050	725	3000K/3500K/4000K	10"	7"	3-1/2"
ELTW0718LAJD1BA	ELTW0718LAJD1BK	21W	1900	1175	3000K/3500K/4000K	17-7/8"	7"	3-1/2"
ELTW0724LAJD1BA	ELTW0724LAJD1BK	25W	2250	1625	3000K/3500K/4000K	24"	7"	3-1/2"