



Gale LED Outdoor Sconce GLEW Series

Features

Ideal use for security and general lighting in outdoor residential, commercial, and hospitality applications. Vertical or horizontal mounting. Fixture mounts to a standard junction box (not included).

Emergency Back-Up (Optional '-BB')

- 90 minute run-time
- 9.6VDC LiFePO4 battery
- 8 watts

Construction

Durable metal construction with powder coat finish. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black or Textured Grey.

Diffuser

White frosted glass diffuser.

Electrical

Input 120-277 VAC / 60 Hz.
0-10V dimming (120-277V), TRIAC (120V).
Minimum starting temp -4° F/ -20°C.

LED

Integrated LED modules capable of producing:
25W = 1425 delivered lumens
29W = 1663 delivered lumens
35W = 2400 delivered lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations.
Title 24/JA8 Compliant (outdoor only).

Option

Emergency battery back-up (24" and 36" ONLY*) Add -BB to end of part number.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.
RESTRICTIONS APPLY BASED ON LOCATION.

Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

Ordering Information:

Black	Textured Grey	LED	Delivered Lumens	CCT	H	W	D
GLEW0518L30UDBK	GLEW0518L30UDTG	25W	1425	3000K	18"	4-1/2"	2-1/2"
GLEW0524L30UDBK*	GLEW0524L30UDTG*	29W	1663	3000K	24"	4-1/2"	2-1/2"
GLEW0536L30UDBK*	GLEW0536L30UDTG*	35W	2400	3000K	36"	4-1/2"	2-1/2"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

