

Glo LED Linear GLOL Series

Features

Perimeter illumination top and bottom with a white acrylic diffuser. For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Extruded aluminum housing. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black, Satin Brass or Satin Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC 60 Hz. Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 40W = 2675 delivered lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.













Ordering Information:

 Black
 Satin Brass
 Satin Nickel
 LED
 Lumens
 CCT
 L
 W
 D

 GLOL4812L30D1BK
 GLOL4812L30D1SN
 GLOL4812L30D1SN
 40W
 2675
 3000K
 47-1/4"
 11-3/4"
 2"