

## **Hermosa LED Pendant HRP Series**

## **Features**

Clear or tinted outer glass pendant is suspended with a 9 foot adjustable cord. Canopy mounts to a standard junction box (not included).

#### Construction

The glass cylinder is 16" tall and 6" in diameter and held together into place by stem and top cap. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

## **Finish**

The canopy is plated in Satin Nickel.

## Diffuser

Glass cylinder pendant is .40" thick. Glass colors include aqua (AQ), clear (CL), clear swirl (CS), and brown (BR).

## **Electrical**

#### **D1** Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

#### D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.

## **LED**

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K or 4000K (CCT). 50,000 hr. LED life, 90 CRI.

## Certification

All fixtures are ETL listed for indoor damp locations.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	

**Limited Quantities Remain. Consult Factory.** 









Clear Swirl

Aqua

# **Ordering Information:**

6" DIA. x 16-3/4" H

	Source					
Series		LED	сст	Driver	Finish	Glass
HRP	1000	L	<b>30</b> 3000K	D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming)	SN Satin Nickel	AQ Aqua
			<b>40</b> 4000K	<b>D2</b> Voltage (120-277V 0-10V Dimming)		CL Clear
						CS Clear Swirl
						BR Brown
	1	'		1		

Example: HRP1000L30D1SNCS

