



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Harvard LED Overbed HVB Series

### Features

Contemporary LED wall mount senior care overbed light with a beautiful combination of wood and shade materials. White acrylic top and bottom diffuser. Provides both ambient and task light with a four way pull switch, standard (120 volt only).

### Construction

The wiring channel is formed from 22-gauge steel and is provided with mounting slots and wiring access. An internal divider provides separate lamp compartments for controlled up light and down light. Fixture can mount horizontally only. Power connections can be made in the fixture wiring channel or in a standard junction box (not included).

### Finish

Solid wood accent detail.

### Diffuser

LumaFuse™ laminated fabric/acrylic shade.

### Electrical

The unit is wired with two UL recognized LED Drivers. The shorter length fixtures produce 1350 source lumens upward, and 2700 down, while the longer fixtures provide 1800 source lumens upward and 3600 down. Four position pull switch (on up, on down, on both, all off) are standard and located near the right side of the fixture. LED nightlight with on/off control pull-switch is included.

### Lamping

Fixture includes LED modules producing a total of 4050 or 5400 source lumens in 3000K CCT. Rated for 50,000 hours

### Certification

cETLus listed for damp locations.

### Options

120-277V universal voltage available without switch and nightlight.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions**  
subject to change without notice.

## Ordering Information:

<b>Jute</b>		<b>Weathered Grey</b>		<b>LED</b>	<b>Source Lumens</b>	<b>CCT</b>	<b>L</b>	<b>H</b>	<b>D</b>
HVB384000L30ENWG-JT		HVB505400L30ENWG-JT		56W	1350 up/2700 down	3000K	38"	4-7/8"	4"
				68W	1800 up/3600 down	3000K	50"	4-7/8"	4"
<b>Linen White</b>		<b>Weathered Grey</b>		<b>LED</b>	<b>Source Lumens</b>	<b>CCT</b>	<b>L</b>	<b>H</b>	<b>D</b>
HVB384000L30ENWG-LW		HVB505400L30ENWG-LW		56W	1350 up/2700 down	3000K	38"	4-7/8"	4"
				68W	1800 up/3600 down	3000K	50"	4-7/8"	4"

**Limited Quantities Remain.  
Consult Factory.**

