

Irvine LED Outdoor Sconce **IRVW Series**

| LOCATION | DATE |
|-------------------|--------------|
| PREPARED BY | QUANTITY |
| COMMENTS | FIXTURE TYPE |
| CATALOG NUMBER | |
| | |



Contemporary Design. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides up/down lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Metal construction Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black finish.

Diffuser

White frosted glass diffuser.

Electrical

Input 120-277 VAC / 60 Hz. 0-10V dimming (120-277V), TRIAC/ELV (120V). Minimum starting temp -4° F/ -20°C.

LED

Integrated LED modules capable of producing: 8W = 500 delivered lumens 15W = 1100 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for outdoor wet locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase. Restrictions apply based on location.

Specifications and dimensions subject to change without notice.

Ordering Information:

| | | Delivered | | | | |
|-----------------|-----|-----------|-------------------------------|-----|--------|--------|
| Black | LED | Lumens | Adjustable CCT | н | W | D |
| IRVW0408LAJUDBK | 8W | 500 | 2700K/3000K/3500K/4000K/5000K | 8″ | 4-3/4" | 5″ |
| IRVW0512LAJUDBK | 15W | 1100 | 2700K/3000K/3500K/4000K/5000K | 12″ | 5-3/8″ | 6-1/2" |





