



Knoll LED Pendant KNOP Series

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
24"	CATALOG NUMBER	



Features

This pendant features rotatable arms to achieve desired alignment. Includes (2) 6" and (4) 12" adjustable stems with swivel on canopy for 60 deg sloped ceiling. For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Metal housing. Standard mounting holes and hardware are included.

The canopy fits over a standard junction box.

Power supply connections must be made inside a junction box (not included).

Canopy - 6" DIA. X 2" H

Finish

Black, Light Antique Brass or Polished Chrome.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) dimmers.

TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:

40W = 1300 delivered lumens

50W = 2200 delivered lumens

60W = 2600 delivered lumens

Adjustable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).

Rated for 50,000 Hrs., 90 CRI.

Certification




All fixtures are cETLus listed for indoor damp locations.

Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

**Specifications and dimensions
subject to change without notice.**



Ordering Information:

Delivered	LED	Lumens	Adjustable CCT	DIA.	H (MAX)	
Black	Light Antique Brass	Polished Chrome	40W 1300 50W 2200 60W 2600	2700K/3000K/3500K/4000K/5000K 2700K/3000K/3500K/4000K/5000K 2700K/3000K/3500K/4000K/5000K	24" 36" 48"	32" 44" 56"
KNOP24LAJUDBK	KNOP24LAJUDLB	KNOP24LAJUDPC				
KNOP36LAJUDBK	KNOP36LAJUDLB	KNOP36LAJUDPC				
KNOP48LAJUDBK	KNOP48LAJUDLB	KNOP48LAJUDPC				