

Knox LED Outdoor Sconce KNXW Series

Features

Multi-faceted metal construction. Down-light illumination. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in Bronze or White.

Diffuser

Recessed frosted glass diffuser.

Electrical

Input 120-277 VAC / 60 Hz. Compatible with 0-10V dimmers. Minimum starting temp -4° F/-20° C.

Lamping

Fixture includes an LED module capable of producing: 12W = 1000 source lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations. ADA Title 24/J8A Compliant


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

	Source						
Bronze	White	LED	Lumens	CCT	Н	W	D
KNXW061010L30D2B7	KNXW061010L30D2WH	12W	1000	3000K	10"	6-1/4"	3-1/2











Limited Quantities Remain. Consult Factory.





