



## Lake LED Ceiling LAKF Series

### Features

Decorative ceiling fixture features a laser cut design and a white acrylic diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

### Bi-Level Motion Sensor (Optional '-MS')

- Built-in daylight sensor
- Detection area, time delay and daylight threshold can be precisely set via DIP switch
- Wide detection area, range up to 50 ft. (16 m) max

### Emergency Back-Up (Optional '-BB')

- 90 minute run-time
- 7.4V 2500 mAh Lithium Ion Battery
- 8 watts

### Construction

Extruded aluminum housing. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

Black, Gold or Painted Nickel finish.

### Diffuser

White acrylic diffuser.

### Electrical

Input 120-277 VAC 60 HZ.  
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

### LED

Integrated LED modules capable of producing:  
30W = 2400 source lumens  
42W = 3200 source lumens  
60W = 5400 source lumens  
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).  
Rated for 50,000 Hrs., 90 CRI.

### Certification

All fixtures are cETLus listed for indoor damp locations.  
Title 24/JA8 Compliant

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

### Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

## Ordering Information:

Black	Satin Brass	Painted Nickel	LED	Delivered Lumens	Adjustable CCT	DIA.	D
LAKF16LAJUDBK	LAKF16LAJUDGD	LAKF16LAJUDNP	30W	2400	2700K/3000K/3500K/4000K/5000K	16"	4"
LAKF20LAJUDBK	LAKF20LAJUDGD	LAKF20LAJUDNP	42W	3200	2700K/3000K/3500K/4000K/5000K	20"	5"
LAKF24LAJUDBK	LAKF24LAJUDGD	LAKF24LAJUDNP	42W	3200	2700K/3000K/3500K/4000K/5000K	24"	6"
LAKF30LAJUDBK	LAKF30LAJUDGD	LAKF30LAJUDNP	60W	5400	2700K/3000K/3500K/4000K/5000K	30"	7"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



GD  
16"



NP  
24"



BK  
30"

