



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Lake LED Pendant LAKP Series



Features

This pendant features a laser cut design with a white acrylic diffuser. Includes (2) 6" and (4) 12" adjustable stems with swivel on canopy for 60 deg sloped ceiling. For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Extruded aluminum housing. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included). Canopy - 1" H x 6-1/4" DIA.

Finish

Black, Gold or Painted Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
30W = 2400 source lumens
42W = 3200 source lumens
60W = 5400 source lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions
subject to change without notice.



Ordering Information:

Black	Satin Brass	Painted Nickel	LED	Delivered Lumens	Adjustable CCT	DIA.	H
LAKP16LAJUDBK	LAKP16LAJUDGD	LAKP16LAJUDNP	30W	2400	2700K/3000K/3500K/4000K/5000K	16"	4"
LAKP20LAJUDBK	LAKP20LAJUDGD	LAKP20LAJUDNP	42W	3200	2700K/3000K/3500K/4000K/5000K	20"	5"
LAKP24LAJUDBK	LAKP24LAJUDGD	LAKP24LAJUDNP	42W	3200	2700K/3000K/3500K/4000K/5000K	24"	6"
LAKP30LAJUDBK	LAKP30LAJUDGD	LAKP30LAJUDNP	60W	5400	2700K/3000K/3500K/4000K/5000K	30"	7"