



Lambert LED Flush Mount LBTF Series

Features

Ornamental metal accents with a grey linen fabric side diffuser.
White bottom acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

The LED pan is white painted steel. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel metal accents.

Diffuser

Grey linen fabric side diffuser.
White acrylic bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
30W = 2100 delivered lumens
40W = 2900 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Options

Emergency Battery Back-Up (add -BB to the end of the model number)
Motion Sensor (add -MS to the end of the model number)
Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)
90 Minute Run-Time

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions

subject to change without notice.

Ordering Information:

Satin Nickel/Grey	LED	Delivered Lumens	Adjustable CCT	DIA.	D
LBTF16LAJUDSNGY	30W	1675	2700K/3000K/3500K/4000K/5000K	17"	4"
LBTF20LAJUDSNGY	40W	2520	2700K/3000K/3500K/4000K/5000K	21"	4"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



BATTERY BACKUP



FLUSH MOUNT