

# Liam LED Outdoor Sconce LEMW Series

# LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE











### **Features**

Modern design. Provides lighting in residential, commercial, and hospitality applications. Fixture mounts to standard junction box (not included).

### Emergency Back-Up (Optional '-BB') for 24"

- 90 minute run-time
- 9.6VDC LiFePO4 battery
- 8 watts

### Construction

Aluminum housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### **Finish**

Black powder coated finish or Painted Nickel fiinish.

### **Diffuser**

White acrylic diffuser.

### **Electrical**

Input 120-277 VAC 60 HZ. 0-10V dimming (120-277V), TRIAC (120V). Minimum starting temp -4 $^{\circ}$  F / -20 $^{\circ}$ C

### Lamping

Fixture includes a LED modules capable of producing: 20W = 700 delivered lumens 25W = 875 delivered lumens Adjustable Color Temp: 2700K, 3000K, 3500K, 4000K or 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

### Certification

All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant

### Warranty

5 Year Limited Warranty: Restrictions apply based on location.

Specifications and dimensions subject to change without notice.



## Ordering Information:

Delivered									
	Black	Painted Nickel	LED	Lumens	Adjustable CCT	Н	W	D	
	LEMW0518LAJUDBK	LEMW0518LAJUDNP	20W	700	2700K/3000K/3500K/4000K/5000K	18"	4-1/2"	5-1/2"	
	LEMW0524LAJUDBK	LEMW0524LAJUDNP	25W	875	2700K/3000K/3500K/4000K/5000K	24"	4-1/2"	5-1/2"	
	LEMW0524LAJUDBK-BB	LEMW0524LAJUDNP-BB	25W	875	2700K/3000K/3500K/4000K/5000K	24"	4-1/2"	5-1/2"	

