

Leia LED Vanity LIAV Series

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE





Features

Simple style elegant geometry. Horizontal or vertical mounting. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel finish.

Diffuser

Frosted white acrylic diffuser.

Electrical

Input 120-277 VAC 60 Hz.

LED

Integrated LED modules capable of producing:

18W = 1700 delivered lumens

26W = 2500 delivered lumens

34W = 3200 delivered lumens

Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).

Rated for 50,000 Hrs., 90 CRI.

Certification


All fixtures are cULus listed for indoor damp locations. $\ensuremath{\mathsf{ADA}}$

Warranty

Limited warranty. This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.





Ordering Information:

Delivered							
Black	Satin Nickel	LED	Lumens	Adjustable CCT	L	Н	D
LIAV2404LAJMVBK	LIAV2404LAJMVSN	18W	1700	2700K/3000K/3500K/4000K/5000K	24-3/4"	4-1/2"	4"
LIAV3604LAJMVBK	LIAV3604LAJMVSN	26W	2500	2700K/3000K/3500K/4000K/5000K	36-3/4"	4-1/2"	4"
LIAV4804LAJMVBK	LIAV4804LAJMVSN	34W	3200	2700K/3000K/3500K/4000K/5000K	48"	4-1/2"	4"