

Nolan LED Sconce NLS Series

Features

Metal accents with a clear outer glass and white acrylic inner diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts standard to junction box (not included).

Construction

A 22-gauge shallow metal pan is made by stamping process and plated. The front plate is 20-gauge steel with decorative metal trim plated. The shade in shade design with clear outer acrylic and white inner diffuser. Fixture has an open top with white acrylic diffuser on bottom. Power supply connections must be made inside a junction box (not included).

Finish

Satin Nickel or Oakley Bronze with clear lacquer finish.

Diffuser

White acrylic interior diffuser is .100" thick. Exterior clear acrylic diffuser is .100" thick. Distance between both diffusers and diffuser assembly is held by a plastic spacer at the bottom of the diffuser.

Electrical

Input 120-277 VAC 60 Hz. 0.14A at 120 VAC. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 17W = 1400 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs. 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

















Satin Nickel

Oakley Bronze





MC - Mounting Center

Ordering Information:

Satin Nickel	Oakley Bronze	LED	Lumens	Adjustable CCT	Н	W	D	MC
NLS061214LAJUDSN	NLS061214LAJUDKB	17W	1400	3000K/3500K/4000K	12-5/8"	6-1/2"	3-7/8"	6-1/2"

Source