



Novara LED NVS Series

Features

Diamond point formed metal. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Vertical or horizontal mounting. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back pan and mounting plate are die-formed steel. Standard mounting holes and hardware included, power supply connection must be made inside junction box (not included).

Finish

Plated satin nickel with clear top coat.

Diffuser

White acrylic.

Electrical

Input 120 VAC / 60 Hz.
Compatible with residential TRIAC and ELV dimming.

LED

Fixture includes an LED module capable of producing:
15.5W = 1200 source lumens, 376 delivered lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	Delivered Lumens	CCT	H	W	D
NVS5131200L30D1SN	15.5W	1200	376	3000K	13"	4-1/2"	3-5/8"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



**Limited Quantities Remain.
Consult Factory.**

