

Novara LED Vanity NVV Series

Features

Metal accents with white acrylic diffuser. Available in 2, 3, or 4 ft. models. Can be mounted horizontal or vertical. Fixture mounts standard to junction box (not included).

Construction

Die-cast metal diffuser bracket, stamped metal backplate. Power supply connections must be made inside a junction box (not included).

Finish

All cast metal components are finished in satin nickel.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC, 60 Hz. Compatible with residential TRIAC and ELV dimming.

LED

Integrated LED (DOB) modules capable of producting: 2-Light model - 31W LED, 2400 source lumens.
3-Light model - 46.5W LED, 3600 source lumens.
4-Light model - 62W LED, 4800 source lumens.
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



Limited Quantities Remain. Consult Factory.





Ordering Information:

Satin Nickel	LED	Lumens	ССТ	L	Н	D
NVV5252400L30D1SN	31W	2400	3000K	25"	4-1/2"	3-5/8"
NVV5373600L30D1SN	46.5W	3600	3000K	37"	4-1/2"	3-5/8"
NVV5494800L30D1SN	62W	4800	3000K	49"	4-1/2"	3-5/8"