

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	_

## Ideal LED Contemporary Oval PIDF Series

## Features

Contemporary framed oval ceiling mount with a metal trim band. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

## Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

#### Finish

Housing is finished in lighting grade white baked gloss enamel paint. Trim ring is Satin Nickel finish.

#### Diffuser

Diffuser is .080" thick vaccum formed smooth white acrylic.

#### Electrical

Input 120-277 VAC, 60 HZ LED. Not compatible with dimmers.

#### Lamping

Integrated LED modules capable of producing: 32W = 3700 source lumens 4000K (CCT) rated for 50,000 hrs., 80 CRI.

#### Certification

All fixtures are cETLus listed for indoor damp locations.

## Warranty


Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase

Specifications and dimensions subject to change without notice.

# **Ordering Information:**

Satin Nickel	LED	Source Lumens	сст	L	w	D
PIDF172900L40MVSN	32W	3700	4000K	32″	17″	4"





MC - Mounting Center

