

Pearl LED Ceiling PRLC Series

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	

SN

SB



Decorative ceiling fixture features fixed arms with 6 white frosted glass diffusers. interior effect. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Steel construction. Light bars are fixed to the center hub. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black, Satin Brass or Satin Nickel finish.

Diffuser

White frosted glass diffusers.

Electrical

Input 120 VAC 60 HZ. Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 35W = 2300 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification


All fixtures are cETLus listed for indoor damp locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions subject to change without notice.





Ordering Information:

		Delivered					
Black	Satin Brass	Satin Nickel	LED	Lumens	ССТ	D	DIA.
PRLC16L30D1BK	PRLC16L30D1SB	PRLC16L30D1SN	35W	2300	3000K	9-1/4″	16″

