

Pearl LED Pendant PRLP Series

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





Features

This pendant features rotatable arms to achieve desired alignment. Includes (3) 12" and (2) 6" adjustable stems with swivel on canopy for 60 deg sloped ceiling. For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications.

This fixture mounts to a standard junction box (not included).

Construction

Metal construcion. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black, Satin Brass or Satin Nickel finish.

Diffuser

White glass diffusers.

Electrical

Input 120 VAC 60 HZ. Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 40W = 2723 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions subject to change without notice.



Ordering Information:

			Delivered						
Black	Satin Brass	Satin Nickel	LED	Lumens	CCT	Н	DIA.		
PRI P24I 30D1BK	PRI P24I 30D1SB	PRI P24I 30D1SN	40\\/	2723	3000K	17"	24"		