



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Pratt LED Outdoor Sconce PRTW Series

Features

Pivoting heads to adjust light direction.
Ideal use for general lighting in outdoor residential, commercial, and hospitality applications. Fixture can be mounted to a standard junction box (not included) on a wall or ceiling.

Construction

Cast metal housing. Back pan is made from 12 gauge stamped aluminum material with matching powder coat finish. Power supply connections must be made inside a junction box (not included).

Finish

Black, Textured Grey or Oil-Rubbed Bronze finish.

Diffuser

Glass diffuser.

Electrical

Input 120 VAC / 60Hz.
Minimum starting temp -4° F/-20° C
Integrated photocell for dusk to dawn operation.

LED

Integrated LED modules capable of producing:
22W = 1900 delivered lumens
Adjustable Choice 3000K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs. 80 CRI.


Certification

All fixtures are cETLus listed for outdoor wet locations.
Title 24/JA8 Compliant

Warranty

5 Year Limited Warranty:
Restrictions apply based on location.

Specifications and dimensions
subject to change without notice.



Ordering Information:

Black	Textured Grey	Oil-Rubbed Bronze	LED	Delivered Lumens	Adjustable CCT	H	W	D
PRTW0905LAJENBK	PRTW0905LAJENTG	PRTW0905LAJENBZ	22W	1900	3000K/4000K/5000K	5"	9"	7-1/2"