



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Rhea LED Outdoor Sconce REAW Series

### Features

This outdoor LED light is ideal for security and general lighting.  
Vertical or horizontal mounting. Fixture mounts to standard junction box (not included).



### Emergency Back-Up (Optional '-BB')

- 90 minute run-time
- 9.6VDC LiFePO4 battery
- 8 watts

### Construction

Durable metal construction with powder coat finish. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### Finish

Black finish.

### Diffuser

White acrylic diffusers.

### Electrical

Input 120-277 VAC 60 HZ.  
0-10V dimming (120-277V), TRIAC (120V).  
Minimum starting temp -4° F / -20°C

### Lamping

Fixture includes a LED modules capable of producing:  
20W = 900 delivered lumens  
25W = 1200 delivered lumens  
30W = 1500 delivered lumens  
40W = 2000 delivered lumens  
Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).  
Rated for 50,000 Hrs., 90 CRI.

### Certification

All fixtures are cETLus listed for wet locations.  
Title 24/JA8 Compliant

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.  
RESTRICTIONS APPLY BASED ON LOCATION.

### Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

## Ordering Information:

Black	LED	Delivered Lumens	Adjustable CCT	H	W	D
REAW0518LAJUDBK	20W	900	2700K/3000K/3500K/4000K/5000K	18"	5"	2-1/8"
REAW0518LAJUDBK-BB	20W	900	2700K/3000K/3500K/4000K/5000K	18"	5"	2-1/8"
REAW0524LAJUDBK	25W	1200	2700K/3000K/3500K/4000K/5000K	24"	5"	2-1/8"
REAW0524LAJUDBK-BB	25W	1200	2700K/3000K/3500K/4000K/5000K	24"	5"	2-1/8"
REAW0536LAJUDBK	30W	1500	2700K/3000K/3500K/4000K/5000K	36"	5"	2-1/8"
REAW0536LAJUDBK-BB	30W	1500	2700K/3000K/3500K/4000K/5000K	36"	5"	2-1/8"
REAW0548LAJUDBK	40W	2000	2700K/3000K/3500K/4000K/5000K	48"	5"	2-1/8"
REAW0548LAJUDBK-BB	40W	2000	2700K/3000K/3500K/4000K/5000K	48"	5"	2-1/8"

