



## Riley Task Lighting RLEU Series

### Features

The RLEU Series is ideal for undercabinet lighting in kitchens, study area and displays with its low profile design. The housing is available in 5 different lengths, ranging from 9" to 40" to handle most application requirements. The RLEU Series includes an array of LEDs, and is linkable up to 500 watts. In addition the units can be direct wired, and attached to the cabinet with 2 captive mounting screws provide for a smoother installation. Multiple knockouts on the top and the back which offers maximum wiring flexibility.

The following accessories are included with each fixture:

- BX/NM cable connector • direct connector

Hardwire Box (ordered separately) recommended for use (when direct wiring the 9" units)

Occupancy sensor (order separately) available for active motion detection

### Construction

Fixture housing is made from extruded aluminum.

### Finish

All exposed metal parts are post painted in white.

### Diffuser

White polycarbonate diffuser.

### Electrical

Input 120-277 VAC 60 Hz. 0-10V dimming (277V).

This product also provides a user selectable switch with 5 color choices - 2700K, 3000K, 3500K, 4000K and 5000K CCT respectively.

High/low switch included.

### LED

Integrated LED modules capable of producing:

5W = 300 delivered lumens

8W = 500 delivered lumens

12W = 800 delivered lumens

16W = 1050 delivered lumens

20W = 1300 delivered lumens

Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).

Rated for 50,000 Hrs., 90 CRI.

### Certification

Fixtures are cULus listed for indoor damp locations and carry a UL rating for undercabinet/convertible/linkable mounting.

Title 24/JA8 Compliant

Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements


### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

### Specifications and dimensions

subject to change without notice.

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



### ACCESSORIES (ORDER SEPARATELY)

RLEC12WH	12" Interconnect cord - White
RLEC24WH	24" Interconnect cord - White
RLEC36WH	36" Interconnect cord - White
RLEC48WH	48" Interconnect cord - White
RLEC72WH	72" Interconnect cord - White
RLEP60WH	60" Cord & Plug - White



## Ordering Information:

Size	White	LED	Delivered Lumens	Adjustable CCT	LPW	L	W	D
9 in.	RLEU9WH	5W	300	2700K/3000K/3500K/4000K/5000K	60	9"	4-1/8"	1"
14 in.	RLEU14WH	8W	500	2700K/3000K/3500K/4000K/5000K	62.5	14"	4-1/8"	1"
22 in.	RLEU22WH	12W	700	2700K/3000K/3500K/4000K/5000K	66.7	22"	4-1/8"	1"
32 in.	RLEU32WH	16W	1050	2700K/3000K/3500K/4000K/5000K	65.6	32"	4-1/8"	1"
40 in.	RLEU40WH	20W	1350	2700K/3000K/3500K/4000K/5000K	65	40"	4-1/8"	1"