LOCATION		DATE	
PREPARED BY		QUANTITY	
COMMENTS		FIXTURE TYPE	
CATALOG NUMBER			

Sanibel LED Flush Mount
SAF Series

Features
This modern double layer drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade. White bottom acrylic diffuser disperses the light.
Ideal use in kitchens, hallways, and anywhere general lighting is needed.
Provides lighting in residential, commercial and hospitality applications.
Fixture mounts to standard junction box (not included).

Construction
The canopy is made of 22-gauge cold rolled steel. The LED pan is white painted. The acrylic diffuser is supported by the inner shade. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish
Stamped metal components are paintable white baked gloss enamel.

Diffuser
Utilizing Lumafuse™ laminated fabric to acrylic.
Jute and Linen White. Matte white acrylic bottom diffuser.

Electrical
Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED
Integrated LED modules capable of producing:
18W = 1400 source lumens
30W = 2400 source lumens
42W = 3200 source lumens
60W = 5400 source lumens
Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs. 90 CRI

Certification
All fixtures are cETLus listed for indoor damp locations.
*Title 24/JA8 Compliant

Options (excludes 16” models)
Emergency Battery Back-Up (add -BB to the end of the model number)
Motion Sensor (add -MS to the end of the model number)
Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)
90 Minute Run-Time

Warranty
Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Jute

Linen White



BATTERY BACKUP

FLUSH MOUNT

Ordering Information:

Jute	Linen White*	LED	Source Lumens	Adjustable CCT	DIA.	D
SAF1614LAJUD-JT	SAF1614LAJUD-LW	18W	1400	2700K/3000K/3500K/4000K/5000K	16″	5-5/8″
SAF1824LAJUD-JT	SAF1824LAJUD-LW	30W	2400	2700K/3000K/3500K/4000K/5000K	18″	5-5/8″
SAF2332LAJUD-JT	SAF2332LAJUD-LW	42W	3200	2700K/3000K/3500K/4000K/5000K	23-1/4″	5-5/8″
SAF3244L5AJUD-JT	SAF3244L5AJUD-LW	60W	5400	2700K/3000K/3500K/4000K/5000K	32″	8-1/2″