



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Salerno LED Flush Mount SALF Series

### Features

Metal ring with finial and a white glass diffuser.  
Ideal use in kitchens, hallways, and anywhere general lighting is needed.  
Provides lighting in residential, commercial and hospitality applications.  
Fixture mounts to standard junction box (not included).



### Construction

The canopy is 22-gauge stamped steel. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

Polished Chrome finish.

### Diffuser

White glass diffuser.

### Electrical

Input 120-277 VAC 60 HZ.  
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.  
TRIAC and ELV dimming only at 120 VAC.

### LED

Integrated LED modules capable of producing:  
17W = 1400 source lumens, 885 delivered lumens  
29W = 2400 source lumens, 1612 delivered lumens  
Adjustable Choice 3000K, 3500K, 4000K (CCT).  
Rated for 50,000 Hrs., 90 CRI.

### Options for 16" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)  
Motion Sensor (add -MS to the end of the model number)  
Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)

### Certification

All fixtures are cETLus listed for indoor damp locations.


### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.


**Specifications and dimensions**  
subject to change without notice.

### Ordering Information:

Polished Chrome	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
SALF13LAJUDPC	17W	1400	885	3000K/3500K/4000K	13-1/2"	5-1/2"
SALF16LAJUDPC	29W	2400	1612	3000K/3500K/4000K	16-1/4"	5-1/2"



FLUSH MOUNT



BATTERY BACKUP