



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Salerno LED Flush Mount SALF Series

Features

Metal ring with finial and a white glass diffuser.
Ideal use in kitchens, hallways, and anywhere general lighting is needed.
Provides lighting in residential, commercial and hospitality applications.
Fixture mounts to standard junction box (not included).

Construction

The canopy is 22-gauge stamped steel. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Polished Chrome finish.

Diffuser

White glass diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
17W = 1400 source lumens, 885 delivered lumens
29W = 2400 source lumens, 1612 delivered lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Options for 16" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)
Motion Sensor (add -MS to the end of the model number)
Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Polished Chrome	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
SALF13LAJUDPC	17W	1400	885	3000K/3500K/4000K	13-1/2"	5-1/2"
SALF16LAJUDPC	29W	2400	1612	3000K/3500K/4000K	16-1/4"	5-1/2"



**Limited Quantities Remain.
Consult Factory.**

